

CLAIMS

1. Method of current management in a battery powered device, the method
5 comprising the following steps:
 - a- comparing the actual supply voltage from the battery with a fixed reference voltage,
 - b- generating a control signal whenever the supply voltage is below the reference voltage,
 - 10 c- use the control signal to reduce the load current in the battery powered device, whereby the supply voltage from the battery will increase,
 - d- repeat steps a,b and c as long as the supply voltage is below the reference voltage.
- 15 2. Method as claimed in claim 1, wherein the battery powered device is an amplifier in a hearing aid, and whereby the repetition frequency of steps a,b and c is higher than the highest audio frequency of the hearing aid.
3. Method as claimed in claim 2 where the reference voltage is above a critical
20 supply voltage of the hearing aid.
4. Method of current management as claimed in claim 1 or 2, wherein the battery is a zinc-air battery.
- 25 5. Method of current management as claimed in claim 1 or 2, wherein the battery is a rechargeable battery.
6. Battery powered device with a battery giving a supply voltage to the device, whereby means are provided for generating a fixed reference voltage and
30 means for comparing the supply voltage with the reference voltage, and where the comparing means are arranged to deliver a control signal to the device whenever the supply voltage is below the reference voltage, and where the

REPLACED BY
ART 34 AMDT

device has means for reducing its current load at the receipt of the control signal.

- 5 7. A battery powered device as claimed in claim 6, where the device is an output amplifier in a hearing aid, and where the comparing means are arranged to conduct the comparing at a repetition frequency, which is above the highest audio frequency of the hearing aid.
- 10 8. A battery powered device as claimed in claim 6, where the battery is a zinc-air battery.
9. A battery powered device as claimed in claim 6, where the battery is a rechargeable battery.

15

REPLACED BY
ART 34 AMDT